



DEPARTMENT OF PURCHASING & CONTRACT COMPLIANCE
Winner 2000- 2006 Achievement of Excellence in Procurement Award
National Purchasing Institute

Jerome Noble, Director



March 19, 2008

Re: Invitation to Bid #08ITB60827C-BL, Uniforms and Gear

Dear Proposer:

Attached is one (1) copy of Addendum 2, hereby made a part of the above referenced **Invitation to Bid #08ITB60827C-BL, Uniforms and Gear.**

Except as provided herein, all terms and conditions in the Request for Proposal referenced above remain unchanged and in full force and effect.

Sincerely,

William E. Long, Jr., CPPB
Chief Assistant Purchasing Agent

**#08ITB60827C-BL,
Uniforms and Gear
Addendum No. 2
Page Two**

This Addendum forms a part of the contract documents and **modifies** the original RFP documents as noted below is to be added to Section 3 of the solicitation:

SPECIFICATIONS FOR ACCEPTABLE RAINWEAR ARE ATTACHED.

ACKNOWLEDGEMENT OF ADDENDUM NO. 2

The undersigned proposer acknowledges receipt of this addendum by returning one (1) copy of this form with the proposal package to the Department of Purchasing & Contract Compliance, Fulton County Public Safety Building, 130 Peachtree Street, Suite 1168, Atlanta, Georgia 30303 by the RFP due date and time, **April 16, 2008**, 11:00 A.M.

This is to acknowledge receipt of Addendum No. 1, _____ day of _____, 2008.

Legal Name of Bidder

Signature of Authorized Representative

Title

| | | |
|--------------------------|-------------------------------|---|
| <u>MATERIALS:</u> | <u>FACE FABRIC:</u> | 100% Polyester |
| | <u>Construction:</u> | Plain Weave |
| | Yarn Count (Deniers) | War p Weft 2 * 150 D 2 * 150 D |
| | Contexture (Yarns/Inch) | War p Weft 53 45 |
| | Weight (Ounces / sq. yd.) | 4.6 +/- 0.2 |
| | Color | Black |
| | <u>MEMBRANE:</u> | Waterproof & Breathable PU membrane (Coated fabrics shall be cause for rejection) |
| | Color | White |
| | <u>BACK KNIT:</u> | Tricot |
| | Color | High Visibility Yellow |
| | <u>3-PLY LAMINATE:</u> | |
| | Weight (Ounces / sq. yd.) | 6.9 +/- .03 |
| | Tensile strength (ISO 1421) | War p Weft > 1150 N > 1000 N |
| | Tear strength (ISO 4674-B) | War p Weft > 90 N > 90 N |

| | |
|-------------------------------------|---|
| <p><u>BASIC STYLING:</u></p> | <p>Shall be a full-length raincoat with raglan style sleeves. Raincoat shall be reversible with one side black and one side high-visibility florescent yellow. Other features shall include: Convertible collar with velcro closure, two side openings with velcro closure, snap front with double closure, velcro cuff closure.</p> |
| <p><u>SLEEVES:</u></p> | <p>Sleeves shall be one-piece – raglan style. Sleeve hems to be ¾” wide. There shall be a tab attached at the inside seam made of face fabric, measuring 2” wide at the base and 1 ½” at the top and 2 ½” in length. There shall be a 2” by 1” strip of velcro (hook side) on the back side of the tab, this will be in line with a 6” by 1” strip of velcro (loop side) attached to the sleeve. The long strip of velcro shall be approximately 1” from edge of sleeve and begin 1 ¼” from side seam and extend around the front of the sleeve. This function is to allow adjustable sleeve closure. There shall also be a snap set approximately 2” from the side seam the backs of the snaps shall show on the dark side of the coat – this is to allow for closure of the sleeve on the high visibility side.</p> |
| <p><u>COLLAR:</u></p> | <p>The collar shall be made of two plies of face fabric. The collar points shall be well shaped and symmetrical. The points of the collar shall be 3 ½” wide and 4” across. There shall be a tab made of two plies of face fabric set into the collar seam at the front edge / neck seam and measuring 3” on top, 2 ½” on bottom and ¾” wide. The tab shall have velcro (hook side) on both side measuring approximately 1 ¼” by ¾”. There shall be a 1” by ¾” piece of velcro (loop side) on the underside of the collar (on the dark side of the jacket) to fasten the tab when not in use. There shall be 2” by ¾” strips of velcro (loop side) attached to both sides of the collar to provide adjustable neck closure when worn on either side.</p> |
| <p><u>SIDE VENTS:</u></p> | <p>Coat shall be designed with side vents for easy access to equipment. The vents will measure approximately 11” and shall be set into side seams of coat and shall be covered by welts extending out 1 ¼”. Closure for the side vents shall be provided by a 4 ½” by ¾” strip of velcro centered on insides of the vent/welt.</p> |
| <p><u>FRONT:</u></p> | <p>The coat shall have a six (6) snap front closure. The top snap shall be 1” (at the center of the snap) from the top of the flap, the other snaps shall be approximately 6 ¼” apart (from center to center). Looking at the dark side of the coat: the left front shall have a double male snap. The right front shall have two flaps measuring 2 ½” wide and will sandwich the left flap with two female snaps. The dark side of the coat shall be constructed with placket front.</p> |

| | |
|---------------------------------|--|
| <u>SEAM STITCHING:</u> | Shoulder, underarm, and side seams shall be double needle chan stitch, all other seams to be single needle construction. |
| <u>WATERPROOFING:</u> | All seams to be waterproofed with waterproofing tape of same manufacturing origin as body goods – waterproof, breathable, membrane. |
| <u>REFLECTIVE TAPE:</u> | 1 ½” 3M® silver reflective tape shall be heat applied to the high visibility side of the coat. There shall be a stripe around each sleeve at the edge of the sleeve and around front and back of coat under the armhole. |
| <u>BADGE TAB:</u> | There shall be a badge tab on the left chest on both sides of the coat and shall be made of the matching material. Badge tab on the dark side shall measure 2 ½” by 7/8” with two metal eyelets 1 3/8” apart – center to center. Badge tab on high visibility side shall be heat sealed onto the coat. Badge tab shall measure 3” by 7/8” wide with two metal eyelets 1” apart – center to center. |
| <u>HOOD:</u> | A cape style hood shall be available – style # 7110. The hood shall be designed to be worn over a ‘Police/Patrol Cap’ and shall have a metal eyelet 2” above seam and centered for attaching insignia typically worn on the cap. Closure of the hood shall be by a 3” by 5/8” strip of velcro. Hood shall be made of the same materials as the coat and shall be reversible. |
| <u>LABELING:</u> | Jacket shall be labeled with the manufacturer, size, and country of origin. |
| <u>LIMITED WARRANTY:</u> | The sample and contract garments shall carry a manufacturers printed warranty hang tag. A sample warranty hang tag must accompany the bid package as well. The tag shall instruct the owner of their rights under the warranty. |

| | | | | | | | | |
|---|---|-----------|-------------|-----------|---------------------|-------------|-------------|------------|
| <p><u>LIMITED WARRANTY (CONT.)</u></p> | <p>The Limited warranty shall contain at minimum the following:</p> <p>Warranty coverage: Manufacturer agrees to warrant to the original purchaser that the product will be free from defects in materials and workmanship for a period of three (3) years from date of purchase. This warranty also guarantees the jacket will remain waterproof for three (3) years.</p> <p>Warranty service: Should a covered product become defective during the warranty period, simply return it to the manufacturer with dated proof of purchase. The manufacturer agrees to repair or replace at its option any item determined to be defective and will return to purchaser at no charge.</p> <p>Limitations: This warranty does not cover abnormal wear and tear, nor the color fastness of fluorescent fabrics, nor damage from chemicals, fire, misuse, accident or negligence. This warranty only applies to the original purchaser of the covered product and is not transferable.</p> | | | | | | | |
| <p><u>STOCK SIZES:</u></p> | <p>XS – 3XL (REGULAR)</p> | | | | <p>M-3XL (LONG)</p> | | | |
| <p><u>MEASUREMENT S:</u></p> | <p>Size:</p> | <p>XS</p> | <p>S</p> | <p>M</p> | <p>L</p> | <p>XL</p> | <p>2XL</p> | <p>3XL</p> |
| | <p>Chest: +/- 1”</p> | <p>46</p> | <p>48.5</p> | <p>51</p> | <p>53.5</p> | <p>56</p> | <p>58.5</p> | <p>61</p> |
| | <p>Sweep : +/- 1”</p> | <p>52</p> | <p>54.5</p> | <p>57</p> | <p>59</p> | <p>61.5</p> | <p>64</p> | <p>66</p> |
| | <p>Back Length – size M: REG=47 LONG=49</p> | | | | | | | |
| | <p>Sleeve Length – size M: REG=19 LONG=20 (+/- .75 inches)</p> | | | | | | | |

| | | |
|--------------------------|-------------------------------|---|
| <u>MATERIALS:</u> | <u>FACE FABRIC:</u> | 100% Polyester |
| | <u>Construction:</u> | Plain Weave |
| | Yarn Count (Deniers) | War p Weft 2 * 150 D 2 * 150 D |
| | Contexture (Yarns/Inch) | War p Weft 53 45 |
| | Weight (Ounces / sq. yd.) | 4.6 +/- 0.2 |
| | Color | Black |
| | <u>MEMBRANE:</u> | Waterproof & Breathable PU membrane (Coated fabrics shall be cause for rejection) |
| | Color | White |
| | <u>BACK KNIT:</u> | Tricot |
| | Color | Florescent Yellow |
| | <u>3-PLY LAMINATE:</u> | |
| | Weight (Ounces / sq. yd.) | 6.9 +/- .03 |
| | Tensile strength (ISO 1421) | War p Weft > 1150 N > 1000 N |
| | Tear strength (ISO 4674-B) | War p Weft > 90 N > 90 N |

| | |
|-------------------------------------|---|
| <p><u>BASIC STYLING:</u></p> | <p>Shall be a mid-length raincoat with raglan style sleeves. Raincoat shall be reversible with one side black and one side high-visibility florescent yellow. Other features shall include: Convertible collar with velcro closure, two side openings with snap closure, snap front with double closure, velcro cuff closure.</p> |
| <p><u>SLEEVES:</u></p> | <p>Sleeves shall be one-piece – raglan style. Sleeve hems to be ¾” wide. There shall be a tab attached at the inside seam made of face fabric, measuring 2” wide at the base and 1 ½” at the top and 2 ½” in length. There shall be a 2” by 1” strip of velcro (hook side) on the back side of the tab, this will be in line with a 6” by 1” strip of velcro (loop side) attached to the sleeve. The long strip of velcro shall be approximately 1” from edge of sleeve and begin 1 ¼” from side seam and extend around the front of the sleeve. This function is to allow adjustable sleeve closure. There shall also be a snap set approximately 2” from the side seam the backs of the snaps shall show on the dark side of the coat – this is to allow for closure of the sleeve on the high visibility side.</p> |
| <p><u>COLLAR:</u></p> | <p>The collar shall be made of two plies of face fabric. The collar points shall be well shaped and symmetrical. The points of the collar shall be 3 ½” wide and 4” across. There shall be a tab made of two plies of face fabric set into the collar seam at the front edge / neck seam and measuring 3” on top, 2 ½” on bottom and ¾” wide. The tab shall have velcro (hook side) on both side measuring approximately 1 ¼” by ¾”. There shall be a 1” by ¾” piece of velcro (loop side) on the underside of the collar (on the dark side of the jacket) to fasten the tab when not in use. There shall be 2” by ¾” strips of velcro (loop side) attached to both sides of the collar to provide adjustable neck closure when worn on either side.</p> |
| <p><u>SIDE VENTS:</u></p> | <p>Coat shall be designed with side vents for easy access to equipment. The vents will measure approximately 11” and shall be set into side seams of coat and shall be covered by welts extending out 1 ¼”. Closure for the side vents shall be provided by two (2) snaps.</p> |
| <p><u>FRONT:</u></p> | <p>The coat shall have a five (5) snap front closure. The top snap shall be 1” (at the center of the snap) from the top of the flap, the other snaps shall be approximately 6 ¼” apart (from center to center). Looking at the dark side of the coat: the left front shall have a double male snap. The right front shall have two flaps measuring 2 ½” wide and will sandwich the left flap with two female snaps. The dark side of the coat shall be constructed with placket front.</p> |

| | |
|---------------------------------|--|
| <u>SEAM STITCHING:</u> | Shoulder, underarm, and side seams shall be double needle chan stitch, all other seams to be single needle construction. |
| <u>WATERPROOFING:</u> | All seams to be waterproofed with waterproofing tape of same manufacturing origin as body goods – waterproof, breathable, membrane. |
| <u>REFLECTIVE TAPE:</u> | 1 ½” 3M® silver reflective tape shall be heat applied to the high visibility side of the coat. There shall be a stripe around each sleeve at the edge of the sleeve and around front and back of coat under the armhole. |
| <u>BADGE TAB:</u> | There shall be a badge tab on the left chest on both sides of the coat and shall be made of the matching material. Badge tab on the dark side shall measure 2 ½” by 7/8” with two metal eyelets 1 3/8” apart – center to center. Badge tab on high visibility side shall be heat sealed onto the coat. Badge tab shall measure 3” by 7/8” wide with two metal eyelets 1” apart – center to center. |
| <u>HOOD:</u> | A cap style cover shall be available – style # 7140. The cover shall be designed to be worn over a ‘Police/Patrol Cap’. Cap shall be made of the same materials as the coat and shall be reversible. |
| <u>LABELING:</u> | Jacket shall be labeled with the manufacturer, size, and country of origin. |
| <u>LIMITED WARRANTY:</u> | The sample and contract garments shall carry a manufacturers printed warranty hang tag. A sample warranty hang tag must accompany the bid package as well. The tag shall instruct the owner of their rights under the warranty. |

| | | | | | | | | |
|---|---|-----------|-------------|-----------|---------------------|-------------|-------------|------------|
| <p><u>LIMITED WARRANTY (CONT.)</u></p> | <p>The Limited warranty shall contain at minimum the following:</p> <p>Warranty coverage: Manufacturer agrees to warrant to the original purchaser that the product will be free from defects in materials and workmanship for a period of three (3) years from date of purchase. This warranty also guarantees the jacket will remain waterproof for three (3) years.</p> <p>Warranty service: Should a covered product become defective during the warranty period, simply return it to the manufacturer with dated proof of purchase. The manufacturer agrees to repair or replace at its option any item determined to be defective and will return to purchaser at no charge.</p> <p>Limitations: This warranty does not cover abnormal wear and tear, nor the color fastness of fluorescent fabrics, nor damage from chemicals, fire, misuse, accident or negligence. This warranty only applies to the original purchaser of the covered product and is not transferable.</p> | | | | | | | |
| <p><u>STOCK SIZES:</u></p> | <p>XS – 3XL (REGULAR)</p> | | | | <p>M-3XL (LONG)</p> | | | |
| <p><u>MEASUREMENT S:</u></p> | <p>Size:</p> | <p>XS</p> | <p>S</p> | <p>M</p> | <p>L</p> | <p>XL</p> | <p>2XL</p> | <p>3XL</p> |
| | <p>Chest: +/- 1”</p> | <p>46</p> | <p>48.5</p> | <p>51</p> | <p>53.5</p> | <p>56</p> | <p>58.5</p> | <p>61</p> |
| | <p>Sweep : +/- 1”</p> | <p>52</p> | <p>54.5</p> | <p>57</p> | <p>59</p> | <p>61.5</p> | <p>64</p> | <p>66</p> |
| | <p>Back Length – size M: REG=32 LONG=34</p> <p>Sleeve Length – size M: REG=19 LONG=20 (+/- .75 inches)</p> | | | | | | | |

| | | |
|------------------------------|---|---|
| <u>MATERIALS:</u> | <u>FACE FABRIC:</u> | 100% Polyester |
| | <u>Construction:</u> | Plain Weave |
| | Yarn Count (Deniers) | War p Weft 2 * 150 D 2 * 150 D |
| | Contexture (Yarns/Inch) | War p Weft 53 45 |
| | Weight (Ounces / sq. yd.) | 4.6 +/- 0.2 |
| | Color | Black |
| | <u>MEMBRANE:</u> | Waterproof & Breathable PU membrane (Coated fabrics shall be cause for rejection) |
| | <u>BACK KNIT:</u> | Tricot |
| | Color | High Visibility Yellow |
| | <u>3-PLY LAMINATE:</u> | |
| | Weight (Ounces / sq. yd.) | 6.9 +/- .03 |
| | Tensile strength (ISO 1421) | War p Weft > 1150 N > 1000 N |
| | Tear strength (ISO 4674-B) | War p Weft > 90 N > 90 N |
| <u>BASIC STYLING:</u> | Slip over Rain Pants. Shell to be Proline Fabric Specified above. Full cut style with elasticized back waistband and adjustable snap closure at waist and legs. | |

| | | | | | | | | | | |
|------------------------------|--|----|---|---|---|----|-----|-----|-----|-----|
| <u>WAISTBAND:</u> | Shall be elasticized. There shall be a 7 ½” vent on each side seam with snap closure at the waistband. To add additional waist adjustability, on each side seam there is one female snap on the front portion of the waistband and two male snaps on the back portion of the waistband. The two male snaps shall be placed 1” apart. | | | | | | | | | |
| <u>LEGS:</u> | Straight leg design, four piece with snap closure at bottom. Snaps shall be placed on inside leg of the trouser spaced 2” from the leg seam on each side. | | | | | | | | | |
| <u>WATERPROOFING:</u> | All seams to be waterproofed with waterproofing tape of same color and manufacturing origin as high visibility goods – waterproof, breathable, membrane. | | | | | | | | | |
| <u>LABELING:</u> | Trousers shall be labeled with the manufacturer, size, and country of origin. | | | | | | | | | |
| <u>SIZING:</u> | Length | XS | S | M | L | XL | 2XL | 3XL | 4XL | 5XL |
| | SHORT | X | X | X | X | | | | | |
| | REG | X | X | X | X | X | X | X | X | X |

**LIMITED
WARRANTY:**

The sample and contract garments shall carry a manufacturer's printed warranty hang tag. A sample warranty hang tag must accompany the bid package as well. The tag shall instruct the owner of their rights under the warranty.

The Limited warranty shall contain at minimum the following:

Warranty coverage: Manufacturer agrees to warrant to the original purchaser that the product will be free from defects in materials and workmanship for a period of three (3) years from date of purchase. This warranty also guarantees the jacket will remain waterproof for three (3) years.

Warranty service: Should a covered product become defective during the warranty period, simply return it to the manufacturer with dated proof of purchase.

The manufacturer agrees to repair or replace at its option any item determined to be defective and will return to purchaser at no charge.

Limitations: This warranty does not cover abnormal wear and tear, nor the color fastness of fluorescent fabrics, nor damage from chemicals, fire, misuse, accident or negligence. This warranty only applies to the original purchaser of the covered product and is not transferable.